


- NOTES:**
- PARTITIONS**
 1. All partitions to be 45mm metal studs, with 12.5mm Soundblock board each side and insulation to the void from raised floor to slab (unless otherwise noted). Taped and filled joints.
 2. Head Detail - recessed shadow gap.
 3. Skirting - Applied MDF, 150 x 18mm nosk, fill and sand cut top edge (allow timber floor to fall under).
 4. All skirting to existing walls to match new.
DOORS
 1. Full height oak veneer solid core doors 45mm thick - homogeneity to Detail.
DOOR FRAMES
 1. Komfor Komline 75 Colour by Dulux Ref: BS 108 21 Uplard
LIGHTING
 1. Remove existing light fittings and transport to Wexham, make good existing plasterboard ceiling. Install new lighting system to detail.
FINISHES
 1. All wall and ceiling finishes shall achieve a Class 1 surface spread of flame classification.
FLOOR FINISHES
F1
 1. Carpet Tiles - Vynbond Timber Grain Super Ref: W17741
 2. Carpet tiles all fixed on low tack adhesive to manufacturers instruction
F2
 1. Timber Floor - Master Flooring, Oak Stature (nosk) 2200 lengths x 120 x 18mm thick by DS Ref: 02479 525031 Floor with
 2. Solid Oak thresholds at junctions with carpet tiles.
F3
 1. Slab Tiles - TFC - 600 x 600 x 12mm Italian Black Raven Stone
 2. To include 20mm Acoustic bedding and form. Other
 3. Mastic/Plastic sheet membrane, All fixed to
 4. manufacturer's instruction, Virocure Limited Tel: 020 7223
 5. 0209 including stainless steel edge trim to threshold.
F4
 1. Entrance matting by Jaymat, Ref: ZIGAZAGA (SUPER II)
 2. colour Anthracite (07) Ref: 0173 864 026
 3. Stamped to accommodate junction to sliver / carpet
F5
 1. Vinyl sheet flooring (non slip) by Altro, Ref: Impredast II
 2. colour: IP2003 Mineral T06-01462 707800
F6
 1. Carpet Tiles - Vynbond 100% WOOL Ref: Flamono 9588
 2. Fix plywood base to accommodate height difference.
F7
 1. Carpet Tiles - Vynbond 100% WOOL Ref: Clava W15595
 2. fixed together into a rug, taped behind and loose lay.

- WALL FINISHES**
 All walls to be W1 unless otherwise noted
W1
 1. Paint finish (off white), Vinyl matt Emulsion by Dulux Ref: 50 YY 83057
W2
 1. Paint finish (Orange), Vinyl matt Emulsion Ref: KCS 52080 V49R
W3
 1. Timber slats Oak (to sample) - to have Class 1 translucent finish
W4
 1. Mosaic, Wall Tiles by Caldeni TileRef: white mat 20mm (grey white adhesive grid) Tel: 0207 731 6098
W5
 1. Graphic Digital Wallpaper (Specification TBD) from
 2. Graphic Digital Ref: 0201 553 5330
 3. To meet with Class 1 Spread of Flame
W6
 1. Paint finish (Green), Vinyl matt Emulsion by Benjamin Moore Colour
 2. Product: 045 Vynbondslat Ref: V15-110
W7
 1. Fix free Issue Stone Tiles

- 1/01**
 Sequential floor numbers per floor



Rev	Description	Date	Initial
E	As Built	15/02/05	DH
D	1 no. Dula wall bay removed from Store, W7 carpet Reference amended.	06/01/05	DH
C	Dula wall bay fixating system positions added to Press room 3, 4, 5, 6 and to Press room 4 & 5. Display units added. Revised furniture layout to central area.	22/12/04	DH
B	Partitions setting out. Fishes. Door numbers and key added.	07/12/04	DH

1/01/01
 Location and number of Data Wall bays, Wall mounted track fixating system with ledgers entries, Contractor to fix Plywood mill to partitions where necessary.

ROWLAND ENVIRONMENTS Design

PRELIMINARY INFORMATION
 APPROVAL CONSTRUCTION
 TENDER AS BUILT

Project
 TIMBERLAND (UK) LTD
 KENAN STREET
 LONDON
 WC2B 4AZ

Drawing
 FIRST FLOOR - GENERAL ARRANGEMENT
 PARTITION SETTING OUT & FINISHES LAYOUT

Date 01/11/04 Scale 1:50 @ A1

Drawn By DH / BK Checked By CR / AW

Dwg. No. 262/01/11 Rev. E

ALL DRAWINGS SHOWN SUBJECT TO SITE SURVEY.
 DO NOT SCALE FROM THIS DRAWING.
 ALL DIMENSIONS TO BE CHECKED ON SITE.
 ANY ERRORS TO BE REPORTED TO THE DESIGNER.